

MSDS

Material Safety Data Sheet

614 PAD CEMENT

EXTREMELY FLAMMABLE

I. PRODUCT IDENTIFICATION

Name: APAC 614 Pad Adhesive
Generic ID: Solvent Borne Mastic Adhesive
DOT Hazard Classification: Class 3 Flammable
Liquid, UN1133
Emergency Telephone CHEMTREC: 800-424-9300

II. HMIS (0 = minimal hazard; 4 = severe)

Health = 3 Flammability = 3 Reactivity = 0
Pers. Prot. Equip: H

III. HAZARDOUS INGREDIENTS

Ingredient (CAS #)	Occ.	Exp.	Lmt.	PEL TLV Units
Petroleum Distillate (proprietary blend)				
Hexane (#110-54-3)	500	50		ppm
Vap. Press. 100 mm @ 60°F				
Toluene (#108-88-3)	100	50		ppm
Lacolene (#64742-89-8)	400	50		ppm
Sara Title III Section 313: Toluene 12% by weight; Cyclohexane, less than 1% by weight				

IV. PHYSICAL DATA

BOILING RANGE: 149°F - 232°F. VAPOR DENSITY: Heavier than air. EVAPORATION RATE: Slower than ether. PERCENT VOLATILE BY WEIGHT: 66%. PERCENT WATER VOLUME: None WT/GAL.: 6.62 lbs. VOC: 525 g/l. Non-Photochemically Reactive

V. FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: OSHA: 1H DOT: Flammable. FLASH POINT: Below 20°F. LEL: 1% EXTINGUISHING MEDIA: Foam, CO₂, Dry Chemical, & Water Fog. UNUSUAL FIRE AND EXPLOSION HAZARDS & SPECIAL FIRE FIGHTING PROCEDURES: Never use welding torch on or near cans (even when empty) because residual solvent fumes can explode violently, with subsequent flash fires. Water may be used to keep fire-exposed containers cool until fire is out. Wear self contained breathing apparatus with full face-piece operated in positive pressure when fighting fires.

VI. HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: Headaches, dizziness, eye, nose, throat and lung distress from vapors. Inhalation of high concentrations may asphyxiate. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. **Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.** No long term laboratory tests to determine chronic effects. Skin irritation and dermatitis may develop from prolonged contact with skin. PRIMARY ROUTES OF ENTRY: Inhalation, ingestion, and direct dermal exposure. MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Current anemia, respiratory tract or liver ailments, and skin conditions. EMERGENCY FIRST AID PROCEDURES: Move person to fresh air and apply artificial respiration if needed. Call physician immediately. In case of eye contact, flush eyes with plenty of water for fifteen minutes. Wash skin thoroughly with soap and water or hand cleaner. **KEEP OUT OF REACH OF CHILDREN AND PETS.**

VII. REACTIVITY DATA

STABILITY: Stable INCOMPATIBILITY (Materials to avoid): None known. HAZARDOUS DECOMPOSITION PRODUCTS: May form toxic materials: carbon dioxide and carbon monoxide, various hydrocarbons of unknown structure. CONDITION TO AVOID: Strong oxidizing agents, sparks, open flame, and excessive heat.

VIII. SPILL OR LEAK PROCEDURES

SPILLS: Spill area should be treated as a hazardous location, open doors and windows, extinguish all sources of ignition, keep untrained persons, children and pets away from area, use explosion proof ventilation equipment. If unsure of proper procedure, evacuate area, open door and windows, and call fire department for assistance. Absorb liquid on paper, vermiculite, floor absorbent, or other absorbent material to clear. Residue from cleanup should be allowed to dry thoroughly in an open well ventilated containment area, before disposal. Dispose of remaining material in accordance with applicable regulations.

IX. SAFE HANDLING & USE INFORMATION

VENTILATION: Extremely flammable. Vapors may ignite explosively or cause flash fire. Adequate fresh air cross ventilation is essential to prevent buildup of vapors to PEL, or an explosive concentration. A solvent odor may be noted until adhesive dries. NOTICE: FOR PROFESSIONAL USE ONLY. FIRE PREVENTION: Vapors are heavy and will flow to any source of ignition. Keep away from flame, heat, and sparks during use and until vapors are gone. Extinguish all flames, including pilot lights. (The surest way to put out gas pilot lights is to turn off the main gas valve.) Turn off all electrical appliances. Disconnect electricity from gas appliances and water heaters - many are fitted with electric pilot lights or "spark ignition systems". Do not use electrical switches, fan or tools, such as electric drills. Do not smoke. RESPIRATORY PROTECTION: Outdoor fresh air cross ventilation normally sufficient. If eye watering, headaches or dizziness are experienced, increase fresh air supply, wear NIOSH approved respiratory equipment, or leave the area. PROTECTIVE GLOVES: To prevent skin contact. EYE PROTECTION: Glasses to avoid splashes. OTHER PROTECTIVE EQUIPMENT: None required. HYGIENIC PRACTICES: Wash skin thoroughly with soap and water or hand cleaner.

X. SPECIAL PRECAUTIONS

STORAGE & HANDLING: Keep away from heat, sparks, flames, and all sources of ignition. OTHER PRECAUTIONS: Use only as directed on label. Close container after each use. Do not reuse container.

XI. TRANSPORTATION DATA

DOT: Regulated X. SHIPPING NAME: Adhesive HAZARD CLASS: Flammable LABEL REQUIRED: Red I.M.C.O.-UN 1133 CLASS: 3

APAC believes that data set forth herein is accurate as of the date hereof, and makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.

revised 09-14-2006

APAC
www.apacadhesives.com