

# TECH DATA

All Purpose Adhesives Co.



## TECHNICAL DATA

- **SHELF LIFE:** One year in unopened container
- **TYPICAL COVERAGE:** Approximately 300 lineal feet of four inch base per gallon.
- **OPEN TIME:** Approximately 20 - 30 minutes; varies with temperature and humidity.
- **COLOR:** Cream
- **STORAGE:** Nonflammable; Store above 32°F
- **CONSISTENCY - VISCOSITY:** Smooth, Medium Paste
- **BASE:** Synthetic Polymer Emulsion
- **V.O.C.:** 0 VOC calculated, based on no solvent added
- **WEIGHT PER GALLON:** 10.9 + .2-
- **PACKAGING:** 4 Gallon, 1 Gallon, 1 Quart, 30 Ounce and 11 Ounce Cartridge

**CLEANUP:** Use water when adhesive is wet. Clean wet or dry with nonflammable Solvent.

**LIMITATIONS:** Protect from freezing. Adhesive is freeze / thaw stable to 10°F. Prolonged low temperatures or multiple freeze/thaw cycles should be avoided.

**CAUTION:** Use adequate ventilation. Avoid prolonged breathing of vapors. After using, be sure to wash your hands thoroughly, particularly before eating. May cause skin and eye irritation. Avoid contact with skin and eyes. Thoroughly wash exposed area with soap and water. Eyes: flush with large amounts of water, lifting upper and lower lids occasionally; call a physician immediately. Ingestion: Do not induce vomiting. Call a physician immediately. Keep container closed. **KEEP OUT OF REACH OF CHILDREN. [Refer to Material Safety Data Sheet (MSDS) for further information.]**

# APAC

All Purpose Adhesive Company  
2424 Lakeland Road • Dalton, GA 30721  
800-747-APAC • Fax: 706-277-4157  
www.apacadhesives.com



# APAC 750 COVE BASE ADHESIVE

ACRYLIC-BASED • NONFLAMMABLE • NONTOXIC • LOW V.O.C.

## DESCRIPTION

APAC ECOlogical 750 is solvent free, nonflammable, freeze-thaw stable, and almost odor free. It can be used where other adhesives might present potential health risks. Suitable for office buildings, hotels, hospitals, schools, restaurants and nursing homes.

750 is a fresh alternative for the installation of rubber and vinyl cove base and has all the features an installer has come to expect from APAC products.

## FEATURES & BENEFITS:

- Acrylic Based
- No Solvents
- No Alcohol, Ethylene Glycol or Ammonia
- Low VOC
- Freeze-Thaw Stable
- Nonflammable
- Anti-Microbial

## WARRANTY:

- Limited Warranty

## USES:

- Rubber, Vinyl Cove Base and TPR Cove Base

## RECOMMEND SUBSTRATES:

- (Use only on structurally sound porous surfaces.) Plaster, drywall, plywood, wood paneling, and masonry

## Trowel Recommendation:

- 1/8" V-Notched Spreader

## DIRECTIONS

### Surface Preparation:

Surface must be clean, dry and free from dust, dirt, wax, grease, loose paint or plaster, old adhesives, etc. Plaster and cement must be thoroughly dry and cured. **Do not apply over nonporous surfaces such as vinyl wall coverings, plastic laminates, or multiple coats of paint, etc.** (Painted surfaces can be nonporous check for porosity.)

## Application:

Adhesive, cove base and room temperature must be at 72°F for 48 hours before and after installation. Spread adhesive with a 1/8" notched spreader on back of base or wall surface. Press base firmly into place within ten minutes after application of adhesive. Using a roller, apply pressure immediately to cove base. Be certain that at least 75% of the base is covered with adhesive. Some vinyl base is unstable and could shrink. If any residue or oily substance appears on the back of the base, wipe with denatured alcohol. Rolled or warped base should lay flat for 24 hours before application.



## ASSOCIATIONS:

