


# Product Information



**DURABOND®**



Formerly  
D-505+

## D-5™ Premium Thin-Set Mortar

### **Product Description:**

DURABOND® D-5™ Premium Thin-Set Mortar is for interior or exterior installations to set all types of ceramic, porcelain, granite, slate, marble, limestone, and dimension stone tiles. Use over properly prepared concrete, structurally-sound, exterior grade plywood (interior/dry use only); cementitious backer board; approved membranes; and existing, well-bonded vinyl/VCT or ceramic tile.

### **Product Benefits:**

- May be mixed with water or DURABOND® D-L16
- Exceeds ANSI A118.1 when mixed with water
- Exceeds A118.4 and A118.11 when mixed with either DURABOND D-L16™ High Strength Additive or DURABOND D-L36™ Flexible Mortar Additive
- Extremely durable
- For interior and exterior installations
- For vertical or horizontal installations
- For residential to heavy commercial applications

### **Surface Preparations:**

Surface must be clean, dry and smooth; free of voids, projections, loose materials, oil, grease, sealers, curing compounds, waxes and all other surface contaminants that may inhibit proper bond.

### **Directions For Use:**

Read and understand data sheet completely before beginning installation. Follow applicable ANSI installation standards.

### **Mixing Instructions:**

Using a slow speed mixer (<150 rpm), mix 5 to 6 quarts of clean potable water, or 6 to 7 quarts of DURABOND D-L16 High Strength or D-L36 Flexible Mortar Additive, to 50 pounds of DURABOND D-5 Premium Thin-Set Mortar. Mix to creamy consistency. Allow mixture to stand 15 minutes, and re-mix prior to application. Do not re-temper by adding more liquid.

For installations over plywood, sheet vinyl/VCT, approved membranes, exterior applications, or when setting porcelain tile, DURABOND D-5 Premium Thin-Set Mortar must be mixed with DURABOND D-L16 High Strength or DURABOND D-L36 Flexible Mortar Additive.

### **Application:**

Apply a thin coat of DURABOND D-5 Premium Thin-Set Mortar with the flat edge of trowel to achieve a good mechanical bond to the substrate. Comb additional mortar with the appropriate size notched trowel. If any evidence of skinning or setting occurs, re-comb mortar with notched trowel. Apply mortar to an area no greater than can be tiled in 20 to 30 minutes. Apply using a twisting motion into a fresh bed of mortar to ensure maximum contact and bond. Periodically check back of tile to ensure proper transfer (interior applications-minimum 80% coverage; exterior, wet, or plywood applications-minimum 95% coverage). A finished mortar bed thickness of 3/32" to 1/8" is required.

D32

### Application Over Plywood:

Maximum joist spacing shall be 16" on center. Plywood shall be Underlayment Exterior Grade or C-C Plugged Exterior Grade plywood (or better). If the existing floor is less than 1" thick, glue and nail 15/32" or 1/2" APA Underlayment Exterior Grade or C-C Plugged Exterior Grade plywood to floor. Glue and nail using 5D or 6D (1-1/2" or 2") cement coated screw shank nails 6" on center along the panel edges and a maximum of 8" on center each way throughout the panel. Allow 1/8" gap between underlayment sheet edges and all areas that abut walls, drains, posts, etc., these areas shall be filled with mortar when tiles are installed. Clean and rough sand the plywood. Due to the limitations of plywood as a substrate, DURABOND D-5 Premium Thin-Set Mortar is not intended for use on plywood in exterior, wet interior, or applications subject to heavy/commercial traffic.

### Application Over Existing Vinyl/VCT Flooring:

Vinyl must be clean and well-bonded to substrate. Do not install over cushion-backed or perimeter-bonded sheet vinyl. Remove any loose pieces of vinyl or flooring. Ensure the exposed substrate is suitable for application.

### **Curing:**

Keep all foot traffic off the installation until tile is firmly set (approximately 12 hours). Set times are dependent upon temperature and humidity.

### **Grouting:**

Depending on ambient, slab, and material temperatures, grouting can generally begin after 12 hours with any quality DURABOND grouting system. Allow 48 hours before grouting with any 100% solids epoxy grout.

### **Clean Up:**

Clean all tools and equipment with soap and water. Do not allow material to dry on surface of tile.

### **Packaging:**

50 lb. bags / 50/pallet (2500 lbs.)

## **PLANT LOCATIONS**

TEMECULA, CA 92590

CONYERS, GA 30207

TWINSBURG, OH 44087

PAULSBORO, NJ 08066

[www.bostikfindley-us.com](http://www.bostikfindley-us.com)

October 2001: Supersedes all previously published literature.

## **SUGGESTED TROWELS & COVERAGE FOR MAXIMUM PERFORMANCE**

Trowel size is suggested to maximize transfer/coverage of mortar. Periodically check coverage during installation. Uneven substrate may require the use of either leveling/patching material, or larger notched trowel for proper coverage of mortar.

Ceramic Mosaics  
Mounted Ceramics  
Coverage 85-100 sq. ft.




4" x 4" & 4" x 8"  
Ceramic & pavers  
Coverage 70-80 sq. ft.



6" x 6", 8" x 8" & 12" x 12"  
Ceramic Quarry tile  
Coverage 50-60 sq. ft.



8" x 8" & 12" x 12"  
Lugged back & Mexican paver tile  
Coverage 35-40 sq. ft.



## **LIMITED WARRANTY**

All statements, technical information and recommendations set forth herein are based on tests which Bostik Findley believes to be reliable. However, Bostik Findley does not guarantee their accuracy or completeness. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. Any sale of this product shall be on terms and conditions set forth on Bostik Findley's order acknowledgement. Bostik Findley warrants that the product conforms with Bostik Findley's written specifications, and is free from defects. BOSTIK FINDLEY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE BUYER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL BOSTIK FINDLEY BE LIABLE FOR DIRECT, CONSEQUENTIAL, ECONOMIC OR OTHER DAMAGES.