


Product Information



DURABOND®



Formerly
D-3001

D-731™ Cove Base Adhesive

Product Description:

DURABOND® D-731™ Cove Base Adhesive is a high performance, firm set, acrylic adhesive. The wet suction of the DURABOND D-731 Cove Base Adhesive is strong enough to hold down corners on cove base. DURABOND D-731 Cove Base Adhesive performs well in schools, offices, retail stores, health care facilities, apartments, homes, hotels, and other similar installations.

Product Benefits:

- Easy trowel application
- Holds Corners
- For use on rubber and vinyl cove base
- Adheres to drywall, wood, particle board, concrete, brick and many other surfaces

Performance Characteristics:

- Fast Grab
- Firm Set
- Excellent Wet Suction

Suggested Uses:

DURABOND D-731 Cove Base Adhesive is ideal for use on rubber and vinyl cove base and may be used over dry substrate surfaces including drywall, latex painted surfaces, concrete, brick, wood and particle board. Installers are recommended to conduct pre-installation bond testing with new or unusual cove base material.

Surface Preparation:

Wall surface must be flat, dry, firm, clean and free of dust, dirt, wax, grease and other foreign material. Vinyl wall covering and old adhesive must be stripped from the bonding area prior to adhering the cove base. Glossy paint must be slightly abraded to a rough surface. Plaster must be dry and fully cured.

PHYSICAL & CHEMICAL CHARACTERISTICS

| | |
|---------------------|----------------------------------|
| Base: | Synthetic Acrylic Latex |
| Vehicle: | Water and Petroleum Hydrocarbons |
| Color: | Off White |
| Solids: | 70.0% by Weight |
| Density: | 11 lbs./gal. |
| Flammability: | Nonflammable |
| Consistency: | Medium Paste |
| Application: | Notched Trowel or Cartridge |
| Adjustability Time: | 25-30 Minutes |
| Set-Up Time: | 30-45 Minutes |
| Shelf Life: | One Year* |
| Freeze-Thaw Stable: | 5 cycles at 0°F |

*Stored in original, tightly sealed container

Application:

Warped or rolled cove base should be laid flat for 24 hours prior to installation. Apply adhesive to the cove base or wall with the recommended trowel or spreader; the recommended trowel size is 3/32"X3/32"X3/32" V-notched. The cove base may be positioned and rolled immediately or within 25 minutes of application. For best results, maintain the adhesive, cove base and room at a stable temperature (65°F-85°F) for 24 hours prior, during, and after installation. Adequate ventilation should be provided for at least 72 hours or until residual odors cannot be detected.

*TIP: When installing cove base, always roll it in the direction of the piece already mounted (never go in both directions), this helps prevent future shrinkage.

Coverage:

| Cove Base Width (in.) | lin. ft./gal. | lin. m./gal. |
|-----------------------|---------------|--------------|
| 2.5 | 400-480 | 121-147 |
| 4 | 250-300 | 76-92 |
| 6 | 166-200 | 50-61 |

SUGGESTED TROWEL FOR MAXIMUM PERFORMANCE



3/32" x 3/32" x 3/32"
V-Notched

Limitations:

- This product is for interior installation only.
- Do not use this product over sandy brown coat plaster or fresh plaster with high moisture content, wallpaper, vinyl wall coverings or other non-porous types of wall coverings.
- When working on glazed surfaces, metal surfaces, or other unfamiliar substrates, installers should conduct a pre-installation test.
- For difficult corners and hard-to-bond surfaces, the use of DURABOND® D-615™ Direct Glue Down Carpet Seam Adhesive is recommended.

Clean Up & Storage:

Remove wet adhesive from cove base and tools with soapy water. Use mineral spirits to remove dried adhesive. The container should be closed between spreading cycles and after use.

Packaging:

DURABOND D-731 Cove Base Adhesive is available in 4 gallon and 1 gallon pails as well as 30 oz. cartridge. For the name of the distributor nearest you contact Customer Service at 1-888-592-8558.



PLANT LOCATIONS

TEMECULA, CA 92590

TWINSBURG, OH 44087

CONYERS, GA 30207

PAULSBORO, NJ 08066

www.bostikfindley-us.com

October 2001; Supersedes all previously published literature.

LIMITED WARRANTY

All statements, technical information and recommendations set forth herein are based on tests which Bostik Findley believes to be reliable. However, Bostik Findley does not guarantee their accuracy or completeness. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. Any sale of this product shall be on terms and conditions set forth on Bostik Findley's order acknowledgement. Bostik Findley warrants that the product conforms with Bostik Findley's written specifications, and is free from defects. BOSTIK FINDLEY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE BUYER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL BOSTIK FINDLEY BE LIABLE FOR DIRECT, CONSEQUENTIAL, ECONOMIC OR OTHER DAMAGES.